

MEMOR™ 11 HEALTHCARE

Improve performance and flexibility for Healthcare workers

FLEXIBILITY TAILORED FOR YOUR WORKFORCE

Memor 11 HC is designed to provide a versatile solution for today's clinical and non-clinical healthcare workforce. With an up-to-date operating system and enhanced processing capabilities, this device delivers superior scanning performance and all-around efficiency with Wi-Fi and Cellular capabilities to always be connected.



RUGGED AND COMPACT DESIGN IN AN ENTERPRISE-GRADE FORM FACTOR

The market-proven, semi-rugged, and compact design of Memor 11 HC follows the highly successful Memor 10 HC providing all the pocketability and comfort that healthcare workers need for their daily activities without worrying about dropping the device as it withstands more tumble hits than most comparable devices in the market.

ADVANCED BATTERY MANAGEMENT AND WIRELESS CHARGING

Long-lasting performance due to its swappable battery and embedded SafeSwap™ Technology which ensures uninterrupted continuity. Its effective wireless charging system provides ultra-reliable contactless charging that helps reduce maintenance, enable efficient charging and avoid microbiologically influenced corrosions of contact pins where pathogens can accumulate.

DESIGNED FOR HEALTHCARE

Memor 11 HC is designed for the Healthcare industry and embeds a chemical resistant enclosure to withstand daily cleaning with harsh disinfectant solutions. Dedicated accessories such as the battery pack and hand strap are designed to have cleaning procedures as well.

ENTERPRISE-READY SOLUTION; A SECURE INVESTMENT

Memor 11 HC is powered by Datalogic Mobility Suite. The device has onboard comprehensive tools for effective deployment, enhanced lock-down security measures, and full Android Enterprise integration, ensuring superior performance and data protection in healthcare environments. These capabilities are instrumental in enhancing the device's usability and safeguarding sensitive data. Asset protection both on hardware and software side with EASEOFCARE post-sales service programs that includes Datalogic Shield™.

FEATURES

- Market-proven design, compact and robust
- Wi-Fi and Cellular 4G will keep the healthcare staff always connected inside and outside patient care facilities
- Superior processing capabilities + 4GB of RAM
- 5-inch capacitive multi-touch HD display
- Android 11 with Google Mobile Services (upgradeable to Android 15)
- Ultra-slim 2D imager enhanced for dark environment performance plus Datalogic's exclusive 'Green Spot' technology for visual good-read feedback.
- Ultra-reliable swappable battery with SafeSwap™ capability and Smart Battery Management
- Contactless wireless charging helps reduce maintenance costs and promotes proper charging of the device
- Chemical resistant enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- Backward compatible with all existing Memor 10 accessories
- Access to full suite of value-added Datalogic Software Applications Tools
- EASEOFCARE Service Plans and Datalogic Shield to extend lifecycle and extend years of protection on the device

INDUSTRY - APPLICATIONS

- **Healthcare:**
 - Bedside care
 - Pharmacy
 - Inventory management
 - Facilities management
 - Hospital supply chain
 - Patient transport
 - Clinical support staff
 - Labs



MEMOR 11 HEALTHCARE

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS		PHYSICAL CHARACTERISTICS
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 d/h/i/k/r/v/w; Wi-Fi alliance Certification; WPA3 (Personal and Enterprise)	Dimensions 15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in
Personal Area Network (WPAN)	Class 2, Bluetooth® V5.0, Low Energy (BLE) Support	Display 5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass
NFC Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica	Keys Physical Keys: 2 side scan keys; Power On/Off; Volume Up/Down; 3 user programmable Android™ keys
WWAN Cellular	LTE-Advanced / 4G+; Cat 6 <ul style="list-style-type: none"> EMEA and ROW Configuration: GSM: Quad band; WCDMA: B1/5/8; FDD_LTE: B1/3/5/7/8/20/28; TDD_LTE: B38/39/40/41 	Weight With Battery: 285.0 g / 10.0 oz
Global Positioning System (GPS)	Integrated Assisted-GPS (A-GPS) Supported Types: GPS, GLONASS, BeiDou	
DECODING CAPABILITY		READING PERFORMANCE
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.	Camera Resolution: 13 megapixels; Illumination: User controllable LED flash; Lens: Auto focus
Digital Watermark Codes	Digimarc® Barcode	
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, Dotcode	Scan Engine 2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Halogen™ DE2102-HP: Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending on bar code density and type; Resolution: Megapixel (1280 x 800 pixels); Illumination: White and Red LEDs (for Digimarc); Aiming: 650 nm VLD; Field of View: 42°H x 26°V
Postal Codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC), USPS Intelligent Mail	Print Contrast (Minimum) 25%
Stacked Codes	Micro-PDF417, PDF417, GS1 Composite, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, OCR (ID Cards, Passport)	Minimum Element Width Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils; PDF: 0.0762 mm / 3 mils; Data Matrix: 0.152 mm / 6 mils
ELECTRICAL		SOFTWARE
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8 V; 4,100 mAh (15.6 Watt-hours)	DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.io
Wireless Charging	10 Watt fast charging	
ENVIRONMENTAL		
Drop Resistance	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/concrete according to IEC 60068-2-32 Method 2 and MIL STD 810H Transit drop test.	Protection Shield - Android Security Updates, Launcher - to lockdown device to kiosk mode, Enterprise Browser - to web-browse only to a set of approved URLs, Integrity KIT - to safeguard HW interfaces
Tumbles	Withstands 1,000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 60068-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 60068-2-32 without rubber boot	Configuration Scan2Deploy Studio – to configure and stage devices, OEMConfig – for OEM/EMM Compatibility, AE QR Code Enrollment – for easy EMM/UEM enrollment
Particulate and Water Sealing	IP65	Development SDKs (Java, Kotlin, Xamarin, .NET MAUI JavaScript), Visual Formatter – a no-code platform for barcode formatting, Wedge – a configurable bar code scanning input method
Chemical Resistance	Chemical cleanser and industrial oil resistant	
Healthcare Cleanable	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks	Optimization SoftSpot – a dragable touch scanner trigger; Logger – to collect advanced device events log; Wi-Fi Guard – to collect Wi-Fi data and statistics; Battery Manager – to select from different charging policies
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F	Additional Features
INTERFACES		
Interfaces	USB-C: High Speed USB 2.0 Host and Client	Provisioning Android Zero Touch, Android Enterprise QR code Enrollment, NFC Bump, EMM Token Enrollment, DPC Identifier Enrollment
SENSORS		UEM/EMM Compatibility Highlight SOTI MobiControl VMWare Workspace One, Microsoft Intune, 42Gears SureMDM, Ivanti Neurons, Ivanti Avalanche, and any OEM Config compliant UEM/EMM
Vibration	Software programmable for duration and intensity	Terminal Emulator and PTT Compatibility Highlight Ivanti Velocity, StayLinked Smart TE, Zello PTT
Magnetometer	Senses orientation (eCompass)	
Accelerometer	3-Axis accelerometer to detect orientation	
*Gyroscope	Senses angular velocity *(Wi-Fi/Cellular model only)	
Ambient Light	Auto adjusts display backlight	
Proximity	Auto deactivates display when close to face	
SAFETY & REGULATORY		SYSTEM
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.	Expansion Slots Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible
Environmental Compliance	Complies to EU RoHS	SIM Slot MicroSIM Standard size
		Memory System RAM: 4 GB; eMMC Flash: 32 GB
		Microprocessor 2 GHz Octa-core
		Operating System Android v11 with GMS / AER (Upgradeable to Android 15)
		Real-Time Clock Time and date stamping under software control
ACCESSORIES		WARRANTY & EASEOFCARE
94A150098 Single Slot Charging Dock	94ACC0387 Cleanable Battery Pack	Warranty 1-Year Factory Warranty
94ACC0204 Rubber Boot	94ACC0203 Cleanable Hand Strap	EASEOFCARE Post-sales service programs for 3- or 5-year coverage on the device and charger

94A150098 Single Slot Charging Dock 94ACC0387 Cleanable Battery Pack 94ACC0204 Rubber Boot 94ACC0203 Cleanable Hand Strap

© 2024 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-MEMOR11-HC-EN Revision C 20240304